

AQUA-QUIP EVO2 STAINLESS STEEL TRIM RING

Thank you for purchasing/installing the P/N: ASS 056 Stainless Steel Trim Ring complete with screws, please take the time to read all the information contained below.

INSTALLATION

- 1** Prior to filling the pool with water. Locate the Aqua-Quip Evo2 Light inside the white Dress Ring that has been built into the pool wall, align the screw holes and hold in place.
- 2** Whilst the Evo2 Light is held in position, locate the Stainless Steel Trim Ring over the face of the Evo2 Light and use two screws provided with the Stainless Steel Trim Ring to secure it and the Evo2 Light to the white Dress Ring. Do not over-tighten and do not use a battery operated screwdriver. The smaller screws provided with the Evo2 Light will therefore not be required.

Note: Although previous kits were supplied with an additional clear lens, this new style lower-profile Stainless Steel Trim Ring does not require an additional clear lens fitted between it and the Evo2 Light. If the pool interior surface is forward of the front of the Evo2 Dress Ring, then the screws supplied with the Stainless Steel Trim Ring may not be long enough. Contact Aqua-Quip for longer Stainless Steel screws.



IMPORTANT: Care and Maintenance

- Do not acid wash or chlorine wash the pool whilst either the Evo2 Light or Stainless Steel Trim Ring are mounted in position. This will cause product failure which will not be covered by warranty.
- Only use the electropolished stainless steel screws provided with the product, or screws provided by Aqua-Quip. Use of inferior quality screws may result in corrosion – voiding the warranty.
- The swimming pool water should be balanced immediately when filled. When adding chemicals to pool water, always add in a diluted manner and keep away from the Stainless Steel Trim Rings.
- Always keep the pool water chemically balanced – seek the assistance of your local pool professional. Out of balance swimming pool water will greatly enhance the likelihood of staining/corrosion of the Stainless Steel Trim Ring and/or stainless steel mounting screws, particularly in salt water pools.
- MOST IMPORTANTLY:** Do not allow chlorine levels to rise above 4ppm (parts per million). Chlorine levels above 4ppm may attack the protective chromium oxide layer on the Stainless Steel Trim Ring and/or stainless steel mounting screws and leave them damaged and susceptible to staining and corrosion.

SPECIFICATIONS

Material	Stainless Steel
Grade	316
Finish	Mirror
Passivation	Electropolished
Outside Diameter	155mm
Screws	2 x CSK 20mm, 316 SS, Electropolished

COPYRIGHT AUTOMATIC POOL CLEANERS (AUSTRALIA) PTY LTD E2TR1p_0217



Automatic Pool Cleaners (Australia) Pty Ltd

40 Percy Street, Auburn NSW 2144
Ph: 02 9643 8338 Fax: 02 9643 8448
www.aquaquip.com.au